



# **OIL INDIA LIMITED**

(A Government of India Enterprise)  
P.O. Duliajan - 786602, Assam, India  
FAX: 0374-2800533; Ph: 0374-2808719;

E-mail: [ranjan\\_barman@oilindia.in](mailto:ranjan_barman@oilindia.in); [erp\\_mm@oilindia.in](mailto:erp_mm@oilindia.in)

## **CORRIGENDUM**

Ref: HM/IP/RB/DID1538L20/04

Dated: 09.07.2019

**Sub: Amendment No. 4 dated 09.07.2019 to Annexure-IA of Tender No. DID1538L20/L3**

Dear Sirs,

This **Amendment No. 4** to the Annexure-IA of the subject Tender has been issued to **amend** the following specifications of **item no. 10** as under in place of existing:

<b>Sl. No.</b>	<b>Existing clause ( with clause no./page number)</b>	<b>Amended Clause</b>
1	Annexure-I page- 4 of 7 If felt necessary bidder may include further items in the above spare list	Annexure-I page- 4 of 7 <del>If felt necessary bidder may include further items in the above spare list.</del>
2	Annexure-I page- 4 of 7 <u>Cost of the spares shall be included with the main item(panel), However the prices of the individual spares shall beshown separately. In the event of an order, final list of the spares to be supplied shall be approved by OIL , after drawing approval.</u>	Annexure-I page- 4 of 7 <u>Cost of the spares shall be included with the main item(panel), However the prices of the individual spares shall be shown separately. In the event of an order, final list of the spares to be supplied shall be approved by OIL, after drawing approval.</u>
3	Annexure-IA page- 2 of 14, Incomers: There will be 2 (two) incomers, with 690V (Ue), 800V (Ui), 50 kA Icu (ICu=Ics) or above breaking capacity rated three pole withdrawable type air circuit breaker or plug-in type moulded case circuit breaker, electronic/ microprocessor	Annexure-IA page- 2 of 14, Incomers: There will be 2 (two) incomers, with 690V (Ue), 800V (Ui), 50 kA Icu (ICu=Ics) or above breaking capacity rated three pole withdrawable type air circuit breaker or plug-in type moulded case circuit breaker, electronic/ microprocessor controlled with LSIG protection with adjustable settings

